



Réf : ECHD010



ÉLINGUE CHAÎNE DE DÉBARDAGE

Désignation	Diamètre du câble mm	Résistance mini à la rupture kg	Longueur / Poids mini réalisable		Poids du m + kg
			m	kg	
 08	08	9 000	2	4	1,490

Réf : ECA0011



ÉLINGUE CÂBLE 1 BRIN À CROCHET COULISSANT À LINGUET

CONFORME À LA NORME EN 13414-1+A2

Désignation	Diamètre du câble mm	CMU en kg facteur M = 0,8	Passage boucle de tête mm	Longueur / Poids mini réalisable		Poids du m + kg
				m	kg	
 11	11	1 000	165 x 83	2	2,130	0,482
 13	13	1 250	195 x 98	2	2,900	0,673
 16	16	2 000	240 x 120	3	5,500	1,020
 19	19	3 000	285 x 143	3	8,500	1,460
 24	24	5 000	360 x 180	4	17,400	2,291

1 boucle nue, 1 boucle cossée - Manchonnée alu - **Acier galvanisé**
CMU établie sur la base âme métallique

Réf : ECA014A



ÉLINGUE CÂBLE PLATE TRESSÉE 8 AUSSIÈRES BOUCLES TRESSÉES NUES



Désignation	Diamètre du câble mm	Dimensions approx. mm		CMU en kg facteur M = 1	Passage boucle mm	Longueur / Poids mini réalisable		Poids du m + kg
		largeur	épaisseur			m	kg	
04	4	50	10	1 200	200 x 100	2	1,800	0,900
05	5	55	12	1 900	240 x 120	2	2,500	1,250
06	6	75	15	2 800	250 x 125	2	4,400	2,200
07	7	90	17	3 800	300 x 150	3	8,000	2,650
08	8	110	20	5 000	350 x 175	3	10,200	3,400
09	9	120	22	6 300	400 x 200	3	12,400	4,130
10	10	130	25	7 700	450 x 225	3	16,500	5,500
12	12	160	30	11 000	500 x 250	4	31,500	7,870
14	14	185	35	15 000	600 x 300	4	43,000	10,750
16	16	210	40	19 800	700 x 350	5	70,200	14,040
18	18	235	45	24 900	800 x 400	5	88,500	17,700
20	20	260	50	30 800	850 x 425	6	131,300	21,880

CONSEIL : Dans certains cas de charges, nous préconisons l'utilisation de cosses extra-renforcées, nous consulter.

Acier galvanisé - CMU établie sur base âme textile (possibilité âme métallique pour gamme CMU supérieure : nous consulter.)

Autres références : **ECA014B** (Boucles cosses arceau) / **ECA014C** (Boucles cosses cœur).

Ref : ECHD010



SKIDDING CHAIN SLING CHAIN SLING

Designation	chain diameter mm	Breaking strength kg	Min effective working length		Weight m + kg
			m	kg	
08	08	9 000	2	4	1,490

Ref : ECA011



1 LEG WIRE SLING WITH SLIDING LATCHHOOK

Conform TO STandard EN 13414-1+A2

Designation	Wire rope mm	WLL - kg factor M = 0,8	Head buckle passage mm	Length / Weight minimum achievable		Weight m + kg
				m	kg	
11	11	1 000	165 x 83	2	2,130	0,482
13	13	1 250	195 x 98	2	2,900	0,673
16	16	2 000	240 x 120	3	5,500	1,020
19	19	3 000	285 x 143	3	8,500	1,460
24	24	5 000	360 x 180	4	17,400	2,291

1 bare loop, 1 thimble loop - With aluminium ferrule- **Galvanised steel**

The WLL is established on the basis of a metal core.

Ref : ECA014A



FLAT BRAIDED WIRE SLINGS 8 HAWSERS WITH TWO BARE EYES



Designation	Wire rope diameter mm	Dimensions. mm		WLL - kg factor M = 1	Loop opening dimensions mm	Length / Weight minimum achievable		Weight m + kg
		width	thickness			m	kg	
04	4	50	10	1 200	200 x 100	2	1,800	0,900
05	5	55	12	1 900	240 x 120	2	2,500	1,250
06	6	75	15	2 800	250 x 125	2	4,400	2,200
07	7	90	17	3 800	300 x 150	3	8,000	2,650
08	8	110	20	5 000	350 x 175	3	10,200	3,400
09	9	120	22	6 300	400 x 200	3	12,400	4,130
10	10	130	25	7 700	450 x 225	3	16,500	5,500
12	12	160	30	11 000	500 x 250	4	31,500	7,870
14	14	185	35	15 000	600 x 300	4	43,000	10,750
16	16	210	40	19 800	700 x 350	5	70,200	14,040
18	18	235	45	24 900	800 x 400	5	88,500	17,700
20	20	260	50	30 800	850 x 425	6	131,300	21,880

Galvanised steel - WLL established on a textile core basis (possibility of metal core for higher WLL range: please consult us).

Other references : **ECA014B** (Loops with arch lugs) / **ECA014C** (Loops with heart lugs).

TIP : For certain loads, we recommend the use of extra-reinforced lugs, please consult us.

We have several raw material suppliers, characteristics are given for information purpose only.

Rif : ECHD010



IMBRACATURA IN CATENA DI TRASPORTO

Designazione	Diametro della catena - mm	Resistenza alla rottura - kg	Lunghezza / Peso minimo realizzabile		Peso m + kg
			m	kg	
08	08	9 000	2	4	1,490

Rif : ECA011



CAVO A 1 FILO CON GANCIO A NOTTOLINO SCORREVOLE

CONFORME ALLA NORMA EN 13414-1+A2

Designazione	Diametro del cavo mm	WLL - kg fattore M = 0,8	Passaggio della grande fibbia mm	Lunghezza / Peso minimo realizzabile		Peso m + kg
				m	kg	
11	11	1 000	165 x 83	2	2,130	0,482
13	13	1 250	195 x 98	2	2,900	0,673
16	16	2 000	240 x 120	3	5,500	1,020
19	19	3 000	285 x 143	3	8,500	1,460
24	24	5 000	360 x 180	4	17,400	2,291

1 fibbia nuda, 1 fibbia con anello metallico - Con puntale in alluminio - **Acciaio zincato**

Il WLL è costituito sulla base dell'anima metallica.

Rif : ECA014A



IMBRAGATURA PIATTA INTRECCIATA 8 GOMENE RICCIOLI INTRECCIATI NUDI



Designazione	Diametro del cavo mm	Dimensioni mm		WLL - kg fattore M = 1	Passaggio delle fibbie mm	Lunghezza / Peso minimo realizzabile		Peso m + kg
		larghezza	spessore			m	kg	
04	4	50	10	1 200	200 x 100	2	1,800	0,900
05	5	55	12	1 900	240 x 120	2	2,500	1,250
06	6	75	15	2 800	250 x 125	2	4,400	2,200
07	7	90	17	3 800	300 x 150	3	8,000	2,650
08	8	110	20	5 000	350 x 175	3	10,200	3,400
09	9	120	22	6 300	400 x 200	3	12,400	4,130
10	10	130	25	7 700	450 x 225	3	16,500	5,500
12	12	160	30	11 000	500 x 250	4	31,500	7,870
14	14	185	35	15 000	600 x 300	4	43,000	10,750
16	16	210	40	19 800	700 x 350	5	70,200	14,040
18	18	235	45	24 900	800 x 400	5	88,500	17,700
20	20	260	50	30 800	850 x 425	6	131,300	21,880

CONSIGLIO : Per alcuni carichi si consiglia l'uso di e extra-rinforzate,.

Acciaio zincato - WLL su base anima tessile (possibilità di anima metallica per gamma WLL più elevata : consultarci).

Altro riferimento : ECA014B (Anelli metallici archetto). ECA014C (Anelli in metallo cuore).